

REAR BLADE



Regular Duty

Up to 80 hp tractors. A complete line of rear blades with moldboard widths from 7 to 9 feet.



NVH-240



... harvesting better products!

Ideal for leveling, gardening, and road maintenance jobs. They are also good for cleaning feed lots.

Cut and roll the soil rather than dragging. Save time, horsepower, and fuel.

All rear blades tilt, offset, and angle.



Tilt the moldboard up or down 22°



Offset adjustment allows 18" left or right (manual or hydraulic).



Total swing angle of 360°

Attachments available:



End plates allow rear blade to hold in material for filling.



Land can be quickly and economically leveled simply by attaching the landleveler to the rear blade and applying a "figure-eight" pattern.



Skid shoes increase the life of the cutting edge and avoid damaging the working surface while cleaning corrals or plowing snow.

SPECIFICATIONS		NVH-210	NVH-240	NVH-270
Moldboard width	(ft)	7	8	9
Approximate weight	(lbs)	677	708	800
King pin diameter	(in)	3		
Moldboard height & thickness	(in)	18" x 1/4"		
Cutting edge		1/2" x 6" high carbon-steel blade, reversible, interchangeable		
Maximum tractor hp	(hp)	65	80	
Hitch		3 - point category II		
Swing angle		15°, 30° and 45°, left or right, 3 forward and 3 reverse positions		
Offset adjustment	(in)	9 or 18 left or right (manual or hydraulic) ¹		
Tilt adjustment		7.5°, 15°, 22.5° up or down		
Total swing angle	(°)	360		
Parking stand		Standard		

¹ Optional hydraulic control requires 3" x 8" standard rod type agricultural hydraulic cylinder.
 * Tecnomec Agrícola, S.A. de C.V. reserves the right to make any changes deemed necessary to the specifications without prior notice.
 * Some pictures show equipment that is not necessarily included as part of the standard machine.

Contact your BISON[®] dealer and find out the many other options available.



www.bison.com.mx
 Carretera a Paso Blanco Km.2 #400
 Col. Vista Hermosa C.P. 20905
 Jesús María, Aguascalientes, México
 Tel. (52) (449) 92 - BISON
 (52) (449) 922 - 4766
 Fax. (52) (449) 922 - 4767