



DISC HARROW

ISON



Designed to work in a simple and safe manner, to be easily set-up and operated. They adapt to different ground condition.

The main chassis, the discs section, the hook and the transportation axis are made in structural steel, which is highly resistat to torque.



It carries out soil preparation, weed control and incorporation of waste tasks.

They have five configuration positions for the attack angle in both disks sections, which allows for flawless harrowing in any kind of terrain.



With the precision screw that makes the balancing of the equipment an easy task.

26" x 1/4" disks optional.

The hook plates may be adjusted so that the device works directly behind the tractor or to its left or right, as required.

SPECIFICATIONS		RHTS 1824	RHTS 2024	RHTS 2224	RHTS 2424	RHTS 2624	RHTS 2824	RHTS 3224	
Number of disks		18	20	22	24	26	28	32	
Disks	in	24" x 1/4" Notched front section plain back section							
Hook		Adjustable, eccentric pull							
Main chassis and disk section	in	4x4 square tube							
Working width	ft	6' 7"	6' 7"	8'	8' 10"	9' 6"	10' 2"	11' 8"	
Attack angle	° Front Section 15, 17, 19, 21 & 23 Back section 17, 19, 21, 23 & 25								
Axis of disks	in	n Squared 1 1/2 bar							
Working depth		Hydraulic controlled							
	raising or lowering the transportation wheels								
No. of balls		6	6	6	8	8	8	8	
Disks cleaners		Adjustables							
Wheels		7.00 x 16							
Cylinder	in				3 x 8				
Approximate weight	lbs	2,756	2,866	2,976	3,086			-	
Required power	hp	60	70	80	90	100	100	100	

*Tecnomec Agrícola, S.A. de C.V. reserves the right to modify the specifications whenever it deems necessary without warning. *Some of the pictures depict equipment that is not necessarily included as part of the standard machinery.

Contact your BISON dealer and find out the many other options available.



Carretera a Paso Blanco Km. 2 No. 400 / Col. Vista Hermosa C.P. 20905 Jesús María, Aguascalientes, México Tel. (449) 92-BISON / Fax. (449) 922 4767