DISC HARROW



RHTSO SERIES

GETS MORE FOR YOUR FIELD









SPECIFICATIONS		RHTSO 1824	RHTSO 2024	RHTSO 2224	RHTSO 2424	RHTSO 2624	RHTSO 2824	RHTSO 3224
Number of discs		18	20	22	24	26	28	32
Discs	in	24 X 1/4 Front section notched, back section plain						
Hook		Adjustable and eccentric pull						
Principal framework and discs sections	in	n P.T.R. 4 × 4						
Width	ft	6' 7"	7' 3"	8'	8' 10"	9' 6"	10' 2"	11' 8"
Attack angle		 Front section 15, 17, 19, 21 & 23 Back section 17, 19, 21, 23 & 25 						
Disc axle	in	Squared bar 1 1/2						
Working depth	Hydraulic controled, and raising or lowering the transportation wheels							
Number of bearings			6				8	
Disc cleaner	Adjustable							
Wheels	7.00 X 16							
Cylinders	in				3 X 8			
Aproximate weight	lbs	2,756	2,864	2,976	3,153	3,439	3,571	3,858
Power required	hp	60	70	80	90	100	110	120

*Tecnomec Agricola, S.A. de C.V. reserves the right to modify the specifications whenever it deems necessary without warning.

*Some of the pictures depict equipment that is not necessarily included as part of the standard machinery.

Contact your BISON dealer and find out the many other options avaliable.

www.bison.com.mx 01 800 52 BISON







0

Main framework, disc sections, attachments and transportation axles are fabricated of structural steel, it offers a high resistance to torque.



Qith five positions for the attack angle in both sections of the disc, which allows a fine flawless harrowing in any type of land.

With a precision screw that makes the balancing of the equipment an easy task.





Oil rowlock.

The hook plates may be adjusted so that the equipment works directly behind the tractor or to its left or right as required.

26" x 1/4" discs optional.