FRONT END LOADER



VH-DTP SERIES

GETS MORE FOR YOUR FIELD





FRONT END LOADER

VH-DTP SERIES




0

Versatile, ruggedly built for hard work and long life.

For 75 - 120 hp tractors. Designed for 2 and 4 WD tractors.

Fixed and adjustable valve stands with joystick or two lever control valve are avaliable.

Mechanical self-leveling keeps attachments level when raising and lowering - stack round bales with ease.



High burst pressure phosphatized hydraulic steel tubing and JIC no-leak fittings are standard.

The optional single-lever control provides fast and smooth lift, lower, and dump cycles, making the loader operation faster, easier, and less fatiguing.



Attachment dump linkage provides greater attachment roll-back and dump angle. In addition, quick-attach components (except VH-900-ER) allow for easy mount and dismount in a matter of minutes.

QuickOn / QuickOff mounting to tractor is accomplished quickly and positive locking prevents movement during operation.



AVAILIABLE ATTACHMENTS	VH-1201-DTP	VH-1501-DTP
1 Forklift	Yes	Yes
2 Round Bale Spear	Yes	Yes
3 Square Bale Spear	Yes	Yes
4 Grapple Fork	Yes	Yes
5 Silage Grab	Yes	Yes

SPECIFICATIONS		VH-1201-DTP	VH-1501-DTP
¹ Maximum lift height	ft	12′4″	12′4″
Clearance with bucket dumped	ft	9'6"	9'6"
¹ Reach at max. height	ft	3′6″	3′6″
Maximum dump angle		107	107
¹ Reach with bucket on ground	ft	7′11″	7′11″
Bucket rollback angle		33	33
¹ Digging depth	in	4	4
¹ Overall height in carry position	ft	6′4″	6′4″
Rollback with loader at full heigh	nt	26	26
² Lift capacity to full height	lbs	2800	3350
Lift and bucket cylinder diamete	er in	2 1/2	3
Traction		2 & 4 WD	2 & 4 WD

1 May vary depending on tractor size and model.2 With 2,450 psi tractor hydraulic pressure system.

*Tecnomec Agrícola, S.A. de C.V. reserves the right to modify the specifications whenever it deems necessary without warning. *Some of the pictures depict equipment that is not necessarily included as part of the standard machinery.

Contact your BISON dealer and find out the many other options available.

www.bison.com.mx 01 800 52 BISON





