HAMMER MILL



MMRB & MMIB SERIES

GETS MORE FOR YOUR FIELD





HAMMER MILL MMRB & MMIB SERIES



SPECIFICATIONS		MMRB20	MMIB20
Height	ft	7' 7"	7' 7"
Width	ft	6' 6"	6' 4"
Cyclon Turn		285	285
Cyclon Turn Width	ft	7' 5"	7' 5"
Lenght	ft	10' 10"	9' 7"
Hammers		90	90
Bands		6	6
Parking stands		2	N/A
Fill costal places		2	2
Sieves included		2 (1/2" y 1/4")	2 (1/2" y 1/4")
Aproximate weigh	lbs	1,058	915
Power required	rpm	540	540
Rotor speed work	rpm	3, 200	3, 200
Chute width	in	20"	20"
Estimated performance (dry stubble)	ton/hr	1.5	1.5
Estimated performance (grains)	ton/hr	4.5	4.5

*Tecnomec Agrícola, S.A. de C.V. reserves the right to modify the specifications whenever it deems necessary without warning.

*Some of the pictures depict equipment that is not necessarily included as part of the standard machinery.

Contact your BISON dealer and find out the many other options available.

www.bison.com.mx 01 800 52 BISON







0

BISON Hammer Mills are designed to maximize the nutritional value of feed.

Built with durable, heavy-gauge materials, Bison Hammer Mills deliver top-quality processed grain with minimum maintenance and low operating costs.

Used for efficient grinding process of diverse products.



A Bison Hammer Mill with 90 hammeres and heavy chassis tow does the job quickly and economically.

The hammers are made from high quality carbon steeel for extra-long life. Variety sizes on sieves according to the mills necessities.

The sliding feed gate controls the amount of grain entering the mill.



This equipment has a security stickers for better funcionality and accident prevention.

Variety sizes on sieves according to the mills necessities.

Counts with security guard in its pulleys and greasers for better lubrication. Includes driveshaft to take power from tractor.

Carretera a Paso Blanco Km. 2 No. 400 / Col. Vista Hermosa C.P. 20905 Jesús María, Aguascalientes, México Tel. (449) 92-BISON / Fax. (449) 922 4767