## **MULTI-TILLER**





**SLC/SDC SERIES** 

GETS MORE FOR YOUR FIELD





## MULTI-TILLER SLC/SDC SERIES



SPECIFICATIONS		SDC-1703	SLC-3220	SLC-T-3420
Number of shanks		3	3	3
Shank width	in	1 1/2	1 1/4	11/4
Number of shank positions		Variable	Variable	Variable
Maximum penetration	in	16	12	16
Working width	ft	6' 3"	7' 3"	7' 3"
Minimum tractor hp required	hp	70-100	80-100	100-140
Pulverizer roller		Standard	Standard	Standard
Pulverizer roller width	ft	7'	7' 3"	7' 3"
Number of discs		3	20	20
Disc diameter	in	17	22	22 <sup>1</sup>
Hitch		3 - point cat. ll	3 - point cat. ll	3 - point cat. Il
Approximate weight	lbs	1410	2200	4320
Total length	ft	7' 4"	9' 2"	21' 3"
Disc angle	0		10, 15, 20	10, 15

\*Tecnomec Agricola, S.A. de C.V. reserves the right to modify the specifications whenever it deems necessary without warning.

\*Some of the pictures depict equipment that is not necessarily included as part of the standard machinery.

Contact your BISON dealer and find out the many other options avaliable.

www.bison.com.mx







0

Optional cleaners keep the discs clean of debris.

Muti-tiller points: rip through terrain by cutting the subsoil horizontally without turing the topsoil.



Multi-tillage system: with only one machine you can prepare the seedbed while mixing the residue, breaking up the toposil, and shattering the compacted subsurface layers.

The two front disc gangs help incorporate residue onto the upper soil layers for better erosion control.



Shanks come with wearable vertical shins and replaceable points.

Ideal for terrain with a moderate level of harvest residue.

01 800 52 BISON