REAR BLADE



REGULAR DUTY SERIES

GETS MORE FOR YOUR FIELD









ESPECIFICACIONES		NVH-210	NVH-240	NVH-270
Moldboard width	ft	7	8	9
Approximate weight	lbs	755	722	789
King pin diameter	in		3	
Moldboard height & thickness	in	19" x 1/4"		
Cutting edge		1/2" x 6" high carbon-steel blade,		
		reversible, interchangeable		
Maximum tractor hp	hp	80 (2WD) & 70 (4WD)		
Hitch		3 - point category ll and ll quick hitch ¹		
Swing angle		Forward or reverse positions.		
		3, up to 45° left or right		
Offset adjustment	in	2, up to 18 left or right (manual).		
		0 to 19	left or right (hydi	raulic) ²
Tilt adjustment	0	3, up to 23° up or down		
Total swing angle	0	360		
Parking stand		Standard		

www.bison.com.mx 01 800 52 BISON







0

Up to 80 hp tractors. A complete line of rear blades with moldboard widths from 7 to 9 feet.

Ideal for leveling, gardening, and road maintenence jobs. They are also good for cleaning feed lots.

Cut and roll the soil rather than dragging. Save time, horsepower, and fuel.



Different angle adjustements and tilt:

Tilt the moaldboard up or down 22°.

Offset adjustment allows 18" left or right (manual or hydraulic)

Total swing angle of 360°.



Attachments avaliable:

End plates allow rear blade to hold in materials for filling.

Skid shoes increase the life of the cutting edge and avoid damaging the working surface while cleaning corrals or plowing snow.

1 Bushings not included. 2 Optional hydraulic control requires 3" x 8" standard rod type agricultural hydraulic cylinder.

*Tecnomec Agrícola, S.A. de C.V. reserves the right to modify the specifications whenever it deems necessary without warning.

*Some of the pictures depict equipment that is not necessarily included as part of the standard machinery.

Contact your BISON dealer and find out the many other options available.