## TECHNOLOGY THAT INCREASES PRODUCTIVITY DISC PLOW





**ADB1 SERIES** 

YOUR STRONGEST ALLY





## **DISC PLOW**

**ADB1 SERIES** 



0

The proper functioning of the disc plow is achieved by combining two or more simple adjustments.

It has two angles of attack for more or less aggressiveness of the implement.



A very versatile disc plow, as it adapts to different conditions and types of existing agricultural soil for a uniform fallow at the required depth.

Steal frame without any cast-iron parts making it stronger and heavier to prevent breaking the disc-holder.



Guide-wheel caps individually adjustable (patent pending).

Three vertical angle adjustment of the disk (used to suit different soil conditions).



SPECIFICATIONS		ADB1-328H2	ADB1-48H2
Hitch type		3-point cat. II	
Number of discs		3	4
Dimension of discs	in	28" x 1/4"	
Reversion		Hydraulic	
Width of cut	in	30"	40"
Width of gauge	in	58"	70"
Transport width	in	49"	57"
Depth of cut	in	16	5"
Horizontal angle of discs	0	38 8	i 42
Vertical angle of discs	0	15, 20 & 25	
Total lenght	in	88	110
Total height	in	44"	
Guide wheel		Adjustable	
Vertical tilt adjustment		Side independent	
Steering angle adjustment		3 positions (-10°, 0° y 10°)	
Arm lenght adjustment	in	4 lenghts 6", 6" 7/8", 7" 3/4", 8" 5/8"	
Depth adjustment		Continuous	
Recommended power	hp	65-80	80-10

\* Tecnomec Agricola, S.A. de C.V. reserves the right to make any changes deemed necessary to the specifications without prior notice.

\* Some pictures may include options that are not a part of the standard equipment.

Contact your BISON dealer for more info and other available options.

www.bison.com.mx



Carretera a Paso Blanco Km. 2 No. 400 / Col. Vista Hermosa C.P. 20905 Jesús María, Aguascalientes, México Tel. +52 (449) 92-BISON / Fax. +52 (449) 922 4767

