

**TECHNOLOGY THAT INCREASES PRODUCTIVITY**

**FINISHING EJECTOR SCRAPER**



**LFES SERIES**

**YOUR STRONGEST ALLY**





BISON

## FINISHING EJECTOR SCRAPER LFES SERIES



The laser mount platform comes as standard equipment.

Wheels are easy to replace, and on independent axles.

Side covers to protect ejector cylinders, reducing maintenance costs.



The ejection system is composed of two lateral cylinders, aided by four rollers and guides to push out material without binding.

All pins have been heat treated to increase strength and durability of the machine.



Heavy Yoke Hitch.

All center and side cutting edges are heavy duty and reversible, to increase life span of wearable parts.

The LFES is equipped with all hydraulic hoses and connection to be operated with or without a laser leveling system or GPS.



SPECIFICATIONS		LFES-10	LFES-12	LFES-14	LFES-16
Capacity	yd <sup>3</sup>	8 yd <sup>3</sup>	10 yd <sup>3</sup>	12 yd <sup>3</sup>	14 yd <sup>3</sup>
Width of Cut	ft	10'	12'	14'	16'
Overall Width	in	11'-4"	13'-14"	15'-4"	17'-4"
Tire size		26 x 12-12	13.5 x 16.1	13.5 x 16.1	13.5 x 16.1
Approximate Weight	lbs	6,300 lbs	10,400 lbs	11,000 lbs	11,600 lbs
HP Requirement	hp	140-160	160-180	180-200	200-220
Hydraulic System Requirements		Two double-acting circuits, with a flow rate of 15 GPM at a pressure of 2200 PSI			

\* Tecnomec Agrícola, S.A. de C.V. reserves the right to make any changes deemed necessary to the specifications without prior notice.

\* Some pictures may include options that are not a part of the standard equipment.

Contact your BISON dealer for more info and other available options.

[www.bison.com.mx](http://www.bison.com.mx)



Carretera a Paso Blanco Km. 2 No. 400 / Col. Vista Hermosa C.P. 20905  
Jesús María, Aguascalientes, México  
Tel. (449) 92-BISON / Fax. (449) 922 4767