

**TECHNOLOGY THAT INCREASES PRODUCTIVITY**

# **DISC HARROW**



**RT-PLUS 1/RT-PLUS 2 SERIES**

**YOUR STRONGEST ALLY**





BISON

## DISC HARROW RT-PLUS 1/RT-PLUS 2 SERIES



Designed to work in a simple and safe way. To be easily set-up and operated. It adapts to different soil conditions.

Main chassis and disc sections are made with 6"x4" steel tubing, providing a high resistant to torque.



Up to 5 configuration positions for the attack angle in both front and rear disc sections allow flawless harrowing in any kind of terrain.

Interchangeable hitch. It is adaptable for any kind of tractor drawbar (clevis or flat type).



The bearings bathed in oil requires less maintenance than greased bearings, its double bearing oarlocks makes the implement structure more resistant than the conventional disc bearings.

Reinforced disc cleaners adapt to the countour of the disc.

Its precision screw makes balancing of the equipment an easy task.



SPECIFICATIONS	RT-PLUS1	RT-PLUS1	RT-PLUS1	RT-PLUS1	RT-PLUS1	RT-PLUS1	RT-PLUS1	RT-PLUS1
	RT-PLUS2	RT-PLUS2	RT-PLUS2	RT-PLUS2	RT-PLUS2	RT-PLUS2	RT-PLUS2	RT-PLUS2
	1624	1824	2024	2224	2424	2624	2824	3224
Number of discs	16	18	20	22	24	26	28	32
Disc diameter and thickness	in 24" x 1/4"							
Hitch type	Oscillating, adjustable, eccentric pull							
Main frame & disc section	in 6" x 4"							
Working width	ft 6'	7'	7.5'	8'	9'	9.5'	10'	11.5'
Attack angle	° Front section 16 & 18,3 positions 20-32, 5 discs positions / Back section 16 & 18,3 positions 20-32, 5 discs positions							
Separation between the discs	in 9"							
Axis discs	in 1", 1/2" Round bar							
Working depth	Hydraulically controlled, raising or lowering the transportation wheels							
Leveling	With spindle screw, located on back end of the parallel bar							
Discs cleaners	Adjustables							
Bearings	Double greaseable reinforced bearing							
No. of bearings	6						8	
Tires	7 x 16							
Cylinder	in 3" x 8"							
Approximate weight	lbs 1,150	1,230	1,320	1,370	1,490	1,610	1,690	1,850
Required power	hp 60	60	70	80	90	100	110	120

\*Tecnomec Agrícola, S.A. de C.V. reserves the right to modify the specifications whenever it deems necessary without warning.

\*Some of the pictures depict equipment that is not necessarily included as part of the standard machinery.

Contact your BISON dealer and find out the many other options available.

[www.bison.com.mx](http://www.bison.com.mx)



Carretera a Paso Blanco Km. 2 No. 400 / Col. Vista Hermosa C.P. 20905  
Jesús María, Aguascalientes, México  
Tel. (449) 92-BISON / Fax. (449) 922 4767