

TECHNOLOGY THAT INCREASES PRODUCTIVITY

SUBSOILER



SB SERIES

YOUR STRONGEST ALLY





BISON

SUBSOILER SB SERIES



The shanks move at any distance between two parallel bars, which reduces the use of power.

Tillage points are optional. This kind of point rips topsoil earth with less movements.



Designed to rip any kind of terrain, permitting a deep penetration breaking up the topsoil and shetter. As a result it helps to absorb water and vitamins from the earth, for a better harvest development.



The main frame has predetermine shank adjustments that makes an easy way to install them.

Available with three, five or seven helms (adjustable for the wait zone).

Arrows of easy replacement.



SPECIFICATIONS		SB-5/3		SB-7/5		
Number of shanks		3	5	5	7	
		15"	15"	15"	15	
		20"	20"	20"	20	
	Distance between hanks	in	25"	25"	25"	
			30"		30"	
		35"				
		40"				
Width		3' 9"	7' 6"	6' 3"	8' 9"	
		5'	8' 4"	8' 4"	11' 8"	
	ft	6' 3"		10' 5"		
		7' 6"		12' 6"		
		8' 9"				
		10'				
Required power	hp	75-100	100-125	100-125	140-175	
Hitch type		cat. II & III		cat. II & III		
Approximate weight	lbs	970		1,367		

*Tecnomec Agrícola, S.A. de C.V. reserves the right to modify the specifications whenever it deems necessary without warning.

*Some of the pictures depict equipment that is not necessarily included as part of the standard machinery.

Contact your BISON dealer and find out the many other options available.

www.bison.com.mx



Carretera a Paso Blanco Km. 2 No. 400 / Col. Vista Hermosa C.P. 20905
Jesús María, Aguascalientes, México
Tel. +52 (449) 92-BISON / Fax. +52 (449) 922 4767